

LED DISPLAY SUPPLIER



COMPANY LED WORLD sarl.
Showroom Halat Highway, 1st Floor, Rahi Rent a Car bldg,
Byblos, Lebanon
Mobile: +961 70 502002 | Tel/Fax: +961 9 478430
www.companyledworld.com

COMPANY LED WORLD sarl.

CATALOGUE

All right reserved CLW.



LED Display Creator

O Enterprise Profile	P01-02
Production Equipment	P03-04
Products	
Ux series (Outdoor full color)	P05-06
Ux series (Indoor full color)	P07-08
U series (Outdoor full color)	P09-10
U series (Indoor full color)	P11-12
T series	P13-14
UMG LED series	P15-16
UP series	P17-18
Standard series	P19-20
Projects	P21-30

CONTENTS



LED Display Creator

Customer Oriented
Sustainable Innovation
Pursuiting Perfection
Ensured Stable Supply Chain



Qiangli Jucai, Brilliant Performance

Company LED World offers a wide range of high quality standard led display products as well as customized solutions. With leading R&D team in this sector, CLW pays full attention to individual requirement from clients, it can work out full package of services from project study, initial product design, up to production and after services and other extended services if needed.

Production, Detection Equipment

Qiangliled has made a huge investment to import the most advanced production equipment such as automatic plug-in machine, automatic glue machine, AOI tester and so on from Japan, U.S.A, German etc. Sophisticated production equipment, perfect detection system, experienced production & technical staff, lean intellectual factory management, all these guarantee Qiangliled products excellent quality and performance.







Certificate & Honor

Qiangliled is member of COEMA, Optoelectronic Association of Fujian and Xiamen. We have won variety of honors and reputation such as 'Outstanding Enterprise for Energy Saving Emission Reduction', 'Tax Star Enterprise', 'Advanced Organization of Safety Production', 'National Torch Project Certificate' and other honorary title. Qiangliled product has passed quality management system and environment protection system such as ISO9001, CE, RoHS and 3C certificates and so on.

Market Distributing Network

High quality products distribution benefits millions of clients. "Channel is King" is a principle in Qiangliled operation. After decades of profoundly endeavor on various market's distributing network construction and development, we have formed a powerful marketing service network in the industry.

Brand, Vision

Inheriting honorable past and committing on creating better sustainable and friendly LED ecosphere, Qiangli Jucai will keep on constructing, integrating and developing industry chain and enrich the profit pattern with long-term partners such as Nationstar, Kinglight, Novastar, Listen Vision, Chuanglian.





Production Equipment

by Qiangli Jucai

Steady Supply

Monthly module output: 5 5million pcs(SMD&DIP)

SMD Module output: 150, 000pcs/day

SMT Line: 42

Automatic Assembly line: 15

Outstanding Quality

Introducing international advanced high-precision testing equipment, professional LED parameter testing system, vibration testing equipment, etc.

• Standard Management

Check every process by 6s

• Equipments


- 1.SMT automatic production line
- 2. Automatic aging line
- 3 Automatic potting line
- 4 Full automatic coating line
- 5 Ai production line
- 6 Panasonic multifunctional machine
- 7 Wave soldering machine
- 8. Double track high-speed chip shooter
- 9. high-speed automatic plug-in machine
- 10 GKG solder paste printer
- 11 Reflow soldering machine
- 12 Automatic chip shooter








Ux series outdoor full color display






S4 module front side



S4 module back side



S6.66 module front side

S6.66 module back side



Available item:

S4, S5, S6, S6.66, S8, S10

Product Features:

Gold wire, good flatness, perfect uniformity and consistency, vivid images, perfect video

Applications:

Specially designed for installation in branding, DOOH(advertising) and retail application.



Specification

Items	S4	S5	S6	S6.66	S8 5s	S10 2s
Driving Mode	1/10 Scan	1/8 Scan	1/8 Scan	1/6 Scan	1/5 Scan	1/2 Scan
Structure Features			LED an	d IC in same PCB		
Pixel Pitch (mm)	4	5	6	6.66	8	10
Module Resolution	80*40	64*32	32*32	48*24	40*20	32*16
Module Size (mm)	320*160	320*160	192*192	320*160	320*160	320*160
Pixel Density	62500	40000	27777	22500	15625	10000
Brightness (cd/m²) High Brightness	6000-6500	6000-6500	6000-6500	6000-6500	6000-6500	6500-7000
Module Weight (Kg)	0.55	0.49	0.35	0.51	0.48	0.48
Max Current (A)	≤ 9.36	≤ 8.69	≤ 6.94	≤ 8.78	≤ 8.38	≤ 9.45
Screen Power (W/m²) Consumption	≤ 753	≤ 679	≤ 753	≤ 686	≤ 655	≤ 738
Optimum Viewing Distance (m)	≥4	≥5	≥6	≥7	≥8	≥10
LED Encapsulation	SMD1921	SMD2727	SMD3535	SMD3535	SMD3535	SMD3535
Attenuation (working 3years)			≤15	%		
MTBF			≥100	00 hours		
Defective Rate			< 0.0003,	it's 0 before delive	ry	
IP Grade			IP65	(Front side)		
Driving IC			Constant	t current driving IC		
Refresh Rate (Hz)			≥1	920		
Optimum Viewing Angle (°)			Horizontal:	: 140°, Vertical: 1	30°	
Gray Scale (Bit)				13		





Ux series indoor full color





S1.53 module front side

S1.53 module back side



Product Model:

Ux1.53, Ux1.66, Ux1.83, Ux2, Ux2.5, Ux3, Ux3.07, Ux4

Product Features

Good flatness, perfect uniformity and consistency, vivid images, perfect video, nationstar goldwire.

Applications

Designed for high-end indoor installation in boardrooms, museums, control rooms, broadcast studios, retail and advertising application.



Items	Ux1.53	Ux1.66	Ux1.83	Ux2	Ux2.5	Ux3	Ux3.07	Ux4	
Driving Mode	1/26 Scan	1/32 Scan	1/29 Scan	1/20 Scan	1/32 Scan	1/32 Scan	1/26 Scan	1/20 Scan	
Pixel Pitch (mm)	1.538	1.666	1.839	2	2.5	3	3.076	4	
Module Resolution	208*104	192*96	174*87	160*80	128*64	64*64	104*52	64*32	
Module Size (mm)	320*160	320*160	320*160	320*160	320*160	192*192	320*160	320*160	
Pixel Density	422500	360000	295664	250000	160000	111111	105625	40000	
Brightness (cd/m²)	≥600	≥600	≥600	≥600	≥600	≥600	≥600	≥600	
Module Weight (Kg)	0.51	0.51	0.52	0.5	0.45	0.28	0.42	0.35	
Max Current (A)	6.5	5.7	4.6	5	5.2	4.3	4.7	5.2	
Screen Power Consumption (W/m²)	≤ 571	≤ 501	≤ 404	≤ 439	≤ 457	≤ 525	≤ 413	≤ 457	
Optimum Viewing Distance (m)	≥1.6	≥1.7	≥1.9	≥2	≥2.5	≥3	≥3	≥5	
LED Type	SME	01010	SMD	1515		S	MD2020		
Driving IC				PWM D	riving IC				
Refresh Rate (Hz)				≥38	340				
Attenuation				≤15	5%				
MTBF		≥10000hours							
Defective Rate			<0	.0003, it's 0	before delive	ery			
Optimum Viewing Angle (°)			Horiz	ontal: 140°,	Vertical: 1	30°			
Gray Scale (Bit)				14-	-16				






U series outdoor full color





U5 module front side

U5 module back side





U8 module front side

U8 module back side





Product Model:

U4, U5, U6, U6.66, U8, U10

Product Features:

Perfect uniformity and consistency with high contrast, light and slim design, wide viewing angle.

Applications:

Specially designed for installation in branding, DOOH(advertising) and retail application



Items	U4	U5	U6	U6.66	U8	U8	U10		
Driving Mode	1/10 Scan	1/8 Scan	1/8 Scan	1/6 Scan	1/4Scan	1/5 Scan	1/2 Scan		
Structure Features			LED a	and IC in same	PCB				
Pixel Pitch (mm)	4	5	6	6.66	8	8	10		
Module Resolution	80*40	64*32	32*32	48*24	32*16	40*20	32*16		
Module Size (mm)	320*160	320*160	192*192	320*160	256*128	320*160	320*160		
Pixel Density/ m²	62500	40000	27777	22500	15625	15625	10000		
Brightness (cd/m²)	5000-5500	4500-5000	4500-5000	4500-5000	5000-5500	4500-5500	5500-6000		
Module Weight (Kg)	0.52	0.46	0.35	0.51	0.3	0.48	0.48		
Max Current (A)	9.36	8.69	6.94	8.78	6.24	8.38	9.45		
Screen Power Consumption (W/m²)	823	679	753	686	762	655	738		
Optimum Viewing Distance (m)	≥4	≥5	≥6	≥7	≥8	≥8	≥10		
LED Type	SN	MD2525		SMD	3535				
Attenuation				≤15%					
MTBF			2	10000hours					
Defective Rate			< 0.0001,	it's 0 before	delivery				
IP Grade			IP6	5 (Front side)				
Driving IC			Consta	nt current driv	ring IC				
Refresh Rate (Hz)		≥1920							
Optimum Viewing Angle (°)		Horizontal: 140°, Vertical: 130°							
Gray Scale (Bit)				13					
Company Led World									






U series indoor full color



640*640 die-casting cabinet front side



640*640 die-casting cabinet back side



Product Model:

U1.53, U1.66, U1.83, U2, U2.5, U3, U3.07, U4

Product Features

Good flatness, perfect uniformity and consistency, vivid images, perfect video performance, wide viewing angle

Applications:

Designed for indoor installation in fashion retail, automotive retail, banking or transit advertising application, but it's equally suited for fixed installation in museum, theater, house worship, indoor sports venue and corporate venues.



Specification

Items	U1.53-pro	U1.66-pro	U1.83-pro	U2-pro	U2.5-pro	U3-pro	U3.076-pro	U4-E
Driving Mode	1/26scan	1/32scan	1/29 scan	1/20 Scan	1/32 Scan	1/32 Scan	1/26 Scan	1/20Scan
Pixel Pitch (mm)	1.53	1.66	1.83	2	2.5	3	3.076	4
Module Resolution	208*104	192*96	174*87	160*80	128*64	64*64	104*52	80*40
Module Size (mm)	320*160	320*160	320*160	320*160	320*160	192*192	320*160	320*160
Pixel Density/ m²	422500	360000	295664	250000	160000	111111	105625	62500
Brightness (cd/m²)	≥500	≥500	≥500	≥500	≥500	≥500	≥500	≥500
Module Weight (Kg)	0.51	0.51	0.53	0.5	0.45	0.28	0.32	0.35
Max Current (A)	6.5	5.7	5.8	5	5.2	4.3	4.7	5.3
Screen Power Consumption (W/m²)	571	501	404	439	457	525	413	465
Optimum Viewing Distance (m)	≥1.6	≥1.7	≥1.9	≥2	≥2.5	≥3	≥3	≥4
LED Encapsulation	SMD101	0	SMD1515			SMI	D2020	
Driving IC		Constant of	current driving	IC		Constant co	urrent driving IC	
Refresh Rate (Hz)				≥3840				≥1920
Attenuation					≤15%			
MTBF				:	≥10000 hours			
Defective Rate		< 0.0001, it's 0 before delivery						
Optimum Viewing Angle (°)	Horizontal: 140°, Vertical: 130°							
Gray Scale (Bit)				15	16			





T series



400*300 die-casting cabinet front side



400*300 die-casting cabinet back side



Product Model:

T1.25, T1.58, T1.66, T1.92

Product Features:

Die-casting aluminum cabinet, high precision stitching, lightweight, fast installation

Refresh rate over 3840HZ, perfect display performance

140°Viewing Angle, same effect on multi-directional viewing

Flicker-free and no graininess

Applications:

High-end ultra HD-LED displays not only suits the traditional LED indoor markets, but also for application including control rooms and boardrooms.



Specification

Items	T1.25	T1.58	T1.66	T1.92			
Driving Mode	1/30scan	1/30scan	1/30 scan	1/26 Scan			
Pixel Pitch (mm)	1.25	1.58	1.66	1.92			
Module Resolution	160*240	160*90	120*180	104*156			
Module Size (mm)	200*300	252.8*142.2	200*300	200*300			
Pixel Density/ m²	640000	400576	360000	270400			
Brightness (cd/m²)	≥500	≥500	≥500	≥500			
Cabinet Weight (Kg)	5.5	4.15	4.26	5.6			
Screen Power Consumption (W/m²)	664	950	625	625			
Optimum Viewing Distance (m)	≥1.3	≥1.58	≥1.7	≥2			
LED Encapsulation	SMD1010	SMD1010	SMD1010	SMD1010			
Driving IC	Constant curr	ent driving IC	Constant curre	nt driving IC			
Refresh Rate (Hz)		≥3840					
Attenuation		≤15%					
MTBF	≥10000 hours						
Defective Rate	< 0.0001, it's 0 before delivery						
Optimum Viewing Angle (°)	Horizontal :	160°, Vertical: 160°	Horizontal : 160° Vertical: 160°	Horizontal : 160° Vertical: 160°			
Gray Scale (Bit)		16					





UMG LED series indoor full color



640*480 UMG LED cabinet front side



640*480 UMG LED cabinet back side



Product Model:

UM1, UM2

Product Features:

Full front maintenance, light and portable, separate installation, one-box multi-purpose, double backup, seamless splicing, efficient heat dissipation, large load, high strength.

Applications:

Designed for indoor installation in boardrooms, museums, control rooms, broadcast studios, retail and advertising application.



UMG LED	UM	11		UM2	
Pixel Pitch(mm)	1.25, 1.379, 1.538, 1	.666, 1.839, 2(20s)	2(40	s), 2.5, 3.076,	4
Configuration		1R1G1B			
Module Quanity(L*W)		2*3			
Cabinet Size(W*H*D)		640mm*480mm*85m	m		
Cabinet Area(sqm)		0.307			
Cabinet Weight(KG)		7.85			
Cabinet Flatness(mm/sqm)		<0.65			
Cabinet Power Configuration		4.5V 50A			
Environment		Indoor			
Contrast(X:1)	5000		3000		
Refresh Rate(Hz)	≥3840			≥1920V	
Optimum Viewing Angle (°)	Horizontal: 140°/Vertical: 16	60° I	Horizontal: 140°	Vertical: 130°	
Gray Scale (Bit)	14-16		13		





U poster series (LED Poster)







Product Model:

UP 2.0, UP 2.5

Product Features:

Beautiful appearance, plug and play, easy to transfer, multi-function control, multiple border colors.

Applications

Designed for installation in shopping malls, restaurants, theaters, airports, government agencies, conference rooms.




U poster series	UP 2.0	UP 2.5						
Pixel Pitch(mm)	2.0	2.5						
Configuration	1R1G1B							
Pixel Density(Dots/set)	256000 Dots/set	163840 Dots/set						
Module Quanity(L*W)	4*5	5						
Resolution	320*800	256*640						
Screen Size(W*H*D)	686mm*1766mm*45mm(Tilt)	694mm*1875mm*45mm(Upright)						
Display Size(W*H)	640*	1600						
Cabinet Weight(KG)	32±1(Tilt)、52	2±1(Upright)						
Cabinet Flatness(mm/sqm)	<	1						
Maximum Current(A)	≤5.	2						
Maximum Consumption(W)	58	35						
Brightness	≥50	0						
Brightness uniformity	≥95	%						
Contrast(X :1)	3000	D: 1						
Refresh Rate(Hz)	≥384	40						
Frame frequency(Hz)	≥6	0						
Gray Scale(Bit)	14~10	6						
Optimum Viewing Angle(°)	Horizontal:14	0°, Vertial :130°						
Power Supply Requirements	Standard AC200V	/ , Custom Made 110V						
Control Mode	Intene	et/ WIFI						
Screen Mode	Async	chronous						
Operation Temperature	≤6	0°C						
Environment Temperature	-20°C ~40°C	10%65%RH						









N 4.81 front side



N 4.81 back side





Product Model:

500*500/500*1000, outdoor: N3.91, N4.81, N5.95 indoor: D2.84, D3.91

Product Features:

Ultra-light weight, ultra-thin, good compatibility, quick installation, reliable performance

Applications:

Designed for indoor and outdoor installation in retail industry, entertainment, conference events, etc.





Specification

	In	door	Outdoor				
Items	D2.84	D3.91	N3.91	N4.81	N5.95		
Cabinet Size		500)*500/ 500*1000)			
Driving Mode	1/22scan	1/16scan	1/16scan	1/13scan	1/7scan		
Structure Features		LED	and IC in same	PCB			
Pixel Pitch (mm)	2.84	3.91	3.906	4.806	5.952		
Module Resolution	88*88	64*64	64*64	52*52	42*42		
Module Size (mm)	250*250	250*250	250*250	250*250	250*250		
Pixel Density/ m²	123904	65536	65536	43264	28224		
Brightness (cd/m²)	≥600	≥600	3500-4000	3500-4000	4500-5000		
Module Weight (Kg)	0.52	0.55	0.68	0.69	0.58		
Screen Power Consumption (W/m²)	576	576	576	720	720		
Optimum Viewing Distance (m)	3	4	4	5	6		
LED Encapsulation	SMD2020	SMD2020	SMD1921	SMD2525	SMD2525		
Driving IC			PWM driving IC	;			
Refresh Rate (Hz)			≥3840				
Optimum Viewing Angle (°)	Horizontal: 140+10°/	Vertical: 130°+10	Horizonta	al: 140+10°/Vertical: 130°+	-10		
Gray Scale (Bit)	14						
Attenuation	≤15%						
MTBF			≥10000hours				
Defective Rate		< 0.0001	1, it's 0 before of	delivery			







BYBLOS CHRISTMAS VILLAGE - RENTAL OUTDOOR - 6 X 3 M



HUNTER REPUBLIC OFEICH - U8 MM - OUTDOOR - 4 X 3 M



CASINO DU LIBAN - U5 MM - OUTDOOR - 3 X 5 M



DAR SULTANI ANTELIAS - U6 MM - OUTDOOR - 6 X 4 M



ANTOINE SALIBA JEWELERY - U6 MM - OUTDOOR - 7 X 3 M



HOMENTMEN CLUB - PERIMETER - 30 SQM







CASINO DU LIBAN - U5 MM - OUTDOOR - 3 X 5 M



CASINO DU LIBAN - WORLD CUP EVENT - RENTAL LED SCREENS



PROVINCIAL ANTELIAS - U5 MM - OUTDOOR - 3 X 2 M



CHERFAN DESIGN - MEDIAGRILLE P10 MM - OUTDOOR - 5 X 4 M



CASINO DU LIBAN - Ux 4 MM - OUTDOOR - 2 X 1 M



MOST STEEL BEIRUT - U5 MM - OUTDOOR - 4 X3 M DOUBLE SIDED







BRUMANA HIGH SCHOOL - U10 MM - OUTDOOR - 3 X 2 M



CASINO DU LIBAN - Ux 4 mm - OUTDOOR - 8 X 3 M



DAR SULTANI HAMRA - U4 MM - INDOOR - 3 X 2 M



CASINO DU LIBAN - Ux 4 MM - OUTDOOR - 2 X 1 M



HOME THATER TV - U 4 MM - OUTDOOR - 2.56 X 1.4 M



DAR SULTANI ANTELIAS - U4 MM - INDOOR - 3 X 2 M







BYBLOS BANK DBAYEH - U8 MM OUTDOOR - 4 X 1.28 M



CASINO DU LIBAN - RENTAL LED SCREEN - NEW YEAR EVE



CALIFOOD - WALLSIGN - U 10 MM - 10 X 7 M



CASINO DU LIBAN - RENTAL LED SCREEN - U4 MM OUTDOOR



CASINO DU LIBAN - M1-56 - LED MESH - 4 X 4 M



J M SUPERMARKET - U5 MM OUTDOOR - 3 X 3 M







L'ABEILLE DOR - U6 MM - OUTDOOR - 3 X 2 M



L'ABEILLE DOR - U6 MM - OUTDOOR - 3 X 2 M



KEYROUZ BAKERY - UX 10 MM - OUTDOOR - 4 X 3 DOUBLE SIDED



MONT FORT GALLERY FANAR - U4 MM - OUTDOOR - 3 X 2 M



OCEAN BLUE - SLIDING DOORS - U5 MM - 4 X 3 M



PROVINCIAL KASLIK - U4 MM - OUTDOOR - 2 X 1.5 M









COMPANY LED WORLD sarl.

Showroom Halat Highway, 1st Floor, Rahi Rent a Car bldg, Byblos, Lebanon Mobile: +961 70 502002 | Tel/Fax: +961 9 478430 www.companyledworld.com

IN PARTNERSHIP WITH





*				